

XP Series Sunshade

STANDARD CONSTRUCTION


- Material: Extruded Aluminum 6063-T6 and/or 6061-T6
- Fascia: Round Tube, .125" (3.2mm) nominal wall thickness
- Blades: XP Blades, 4" (102mm) or 6" (152mm) deep, .081" (2.1mm) nominal wall thickness
- Outriggers: Flat Bar, .25" (6.4mm) or .375" (9.5mm) nominal wall thickness
- Mounting Brackets: Extruded Aluminum Tee
- Finish: Mill

OPTIONAL ACCESSORIES

- Aluminum suspension rods
- Segmented or radius formed components
- All sizes are custom fabricated to meet project requirements
- **Tube or Channel Outriggers**

FINISHES

- 2 coat fluropolymer: Fluropon Pure® 70% PVDF (AAMA 2605)*
- 3 coat fluropolymer: Fluropon Pure® 70% PVDF (AAMA 2605)*
- Anodic finishes: Class I & Class II, Clear and Bronze Spectrum
- Prime coat



SUGGESTED SPECIFICATIONS

General: Furnish and install where indicated on drawings XP Series Sunshade as manufactured by Industrial Louvers, Inc., Delano, MN.


Material: Blades to be fabricated from 6063-T6 extruded aluminum louver blades, minimum wall thickness .081". Fascia shall be fabricated from .125" extruded aluminum tubes. Outriggers shall be fabricated from extruded aluminum flat bar, minimum wall thickness of .25". Suspension rods (as required) shall be 3/4" diameter aluminum rod. Mounting brackets shipped loose.



Horizontal Section

Sunshades shall be installed in accordance with manufacturer's recommended attachment method and in accordance with state and federal building codes.

Qty.	Size: Actual M.O. Width Height		Mullion Type	No. of Sections	Notes
	vviatri	пеідпі			
	Sill flashing:		Project:		
	Screen:		Location:		
	Finish:		Architect:		
	Color:		Representative:		
	Other:		Date:	Date: Job #:	





Typical Assembly



CATALOG NO. XP Series